


Maintenance switch,  
plastic enclosed



IP65

Connection  
diagram

Type



Other configurations and sizes on request

3-pole

RLT 16/ 3PM-D1/ Z33

RLT 25/ 3PM-D1/ Z33

RLT 32/ 3PM-D1/ Z33

RLT 40/ 3PM-D1/ Z33

RLT 63/ 3PM-D2/ Z33


RLT 80/ 3PM-D2/ Z33

RLT 100/ 3PM-D3/ Z33

RLT 125/ 3PM-D3/ Z33

RLT 180/ 3K4/ Z20

RLT 250/ 3K4/ Z20



4-pole

RLT 16/ 4PM-D1/ Z33

RLT 25/ 4PM-D1/ Z33

RLT 32/ 4PM-D1/ Z33

RLT 40/ 4PM-D1/ Z33

RLT 63/ 4PM-D2/ Z33

RLT 80/ 4PM-D2/ Z33

RLT 100/ 4PM-D3/ Z33

RLT 125/ 4PM-D3/ Z33

RLT 180/ 4K4/ Z20

RLT 250/ 4K4/ Z20



6-pole

RLT 20/ 6PM-D1/ Z33

RLT 25/ 6PM-D2/ Z33

RLT 32/ 6PM-D2/ Z33

RLT 40/ 6PM-D2/ Z33

RLT 63/ 6PM-D3/ Z33


RLT 80/ 6PM-D3/ Z33

RLT 100/ 6PM-D3/ Z33


RLT 125/ 6PM-D3/ Z33

RLT 180/ 6K4/ Z20

RLT 250/ 6K4/ Z20



|       | I <sub>th</sub><br>A | AC23<br>kW<br>(3x400V) | AC3<br>kW | U<br>V | connection cross<br>mm <sup>2</sup> |
|-------|----------------------|------------------------|-----------|--------|-------------------------------------|
| LT16  | 16                   | 7,5                    | 5,5       | 690    | 6                                   |
| LT25A | 25                   | 9,5                    | 7,5       | 690    | 6                                   |
| LT32  | 32                   | 11,5                   | 9,5       | 690    | 16                                  |
| LT40  | 40                   | 20,0                   | 11,0      | 690    | 16                                  |
| LT63  | 63                   | 22,0                   | 18,5      | 690    | 35                                  |
| LT80  | 80                   | 30,0                   | 22,0      | 690    | 35                                  |
| LT100 | 100                  | 37,0                   | 30,0      | 690    | 50                                  |
| LT125 | 125                  | 45,0                   | 37,0      | 690    | 50                                  |
| LT180 | 180                  | 90,0                   | 75,0      | 690    | 185                                 |
| LT250 | 250                  | 132,0                  | 110,0     | 690    | 185                                 |
| H11   | 10                   |                        |           | 240    | 4                                   |



Enclosures

Sheet metal  
enclosures and  
EMC-accessories

IP65

| TYPE      | A  | C   | F   | L   | Knockouts                          |
|-----------|----|-----|-----|-----|------------------------------------|
| PM-D1/Z33 | 66 | 100 | 140 | 81  | 4 x M25, 4 x M20                   |
| PM-D2/Z33 | 66 | 146 | 176 | 104 | 4 x M32/40, 4 x M20                |
| PM-D3/Z33 | 90 | 302 | 212 | 137 | 4 x M50/63, 6 x M20                |
| K4/Z33    | 90 | 373 | 373 | 230 | 2 x M40/63, 2 x M32/50, 4 x M25/40 |